

MULTI - FORMAT LCD RACK MONITOR

PRM-702



12G-Dual 7" LCD

3RU Multi-Channel Rack Monitor



- | | |
|-------------------------|--------------------------|
| 12G-SDI | Waveform |
| Blue Only | Vector Scope |
| HDR | Internal Pattern |
| H/V Delay | Tally (3 Colors) |
| Scan (Zero, Over) | User Preset Save/Load |
| Audio Level Meter | 3D LUT |
| Markers (Custom Marker) | Gamma |
| Time Code | RS-422 IN/OUT |
| UMD (TSL 3.1) | Remote (GPI Control) |
| Aspect | USB(Update, Calibration) |

Specifications

Spec		PRM-702
Screen number / Rack Size(19")		Dual / 3RU
Display	Size	7"
	Resolution	1920 x 1200
	Active Area (W x H)	151.2mm (W) X94.5(H)mm
	Pixel Pitch	0.078mm x 0.078mm
	Color	16.7M
	Viewing Angle	160(H), 160(V)
	Luminance of White	1000cd/m ²
Contrast		1200:1
Input	SDI	2 x 12G SDI
	HDMI®	1x HDMI® 2.0
Input Signal Format	SMPTE ST 2082-10(12G Single)	2160p(60/59.94/50/30/29.97/25/24/23.98)
	SMPTE ST 2081-10(6G Single)	2160p(30/29.97/25/24/23.98)
	SMPTE ST 425-AB	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST 274	1080p(30/29.97/25/24/23.98/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE ST 296	720p(60/59.94/50)
	SMPTE ST 260	1920 x 1035i(60/59.94)
	SMPTE ST 2048	2048 x 1080p(24/23.98/24sF/23.98sF)
	SMPTE ST 125	480i(59.94)
	ITU-R BT.656	576i(50)
HDMI®	HDMI® 2.0 2160p(60)	
Output	SDI	1 x 12G SDI(A,B Selecte)
Audio	Audio Out	1 x Phone Jack
	Speaker	2 x STEREO
Control	RS-422	o
	Remote (GPI Control)	o
	USB(Update, Calibration)	For Firmware Update, Color Calibration
General	Power Requirements	DC12V / 5A
	Power Consumption	52W
	Operating Temperature	0 ~ 40°C(32°F~104°F)
	Operating Humidity	20% ~ 80% RH
	Dimensions (with RMK)	476.5 x 132.3 x 58.5 mm / 18.88 x 5.2 x 2.30 inch
	Weight	2.5kg / 5.511lbs
	Accessories	DC Power Adapter / Power Cable

* Specifications are subject to change without prior notice for the product quality improvement.

postium® **POSTIUM KOREA Co., Ltd.**
www.postium.com
sales@postium.com